



Radiation Products Design, Inc.

5218 Barthel Industrial Drive

Albertville, MN 55301

www.rpdinc.com

Phone: 800-497-2071 Fax: 763-497-2295

**RPD is an
authorized distributor**

RPD Product Information

Item Number Description

870-708	Styrofoam Blocks 3/4"x8"x8" 55/Cs (25 PSI)
870-710	Styrofoam Blocks 3/4"x10"x10" 36/Cs (25PSI)
870-711	Varian Clinacomp-100 Styrofoam Blocks - 64/Cs
871-008	Styrofoam Blocks 1"x8"x8" (25PSI) 48/Cs
871-010	Styrofoam Blocks 1"x10"x10" 36/Cs (25PSI)
873-008	+ Styrofoam Blocks 3"x8"x8" 72/Cs (40PSI)
873-010	+Styrofoam Blocks 3" x10"x10" 48/Cs (40PSI)
873-012	+Styrofoam Blocks 3"x12"x12" (40PSI) 32/Cs
873-108	Styrofoam Blocks 4"x8"x8" 36/Cs (40PSI)
873-110	Styrofoam Blocks 4"x10"x10" 20/Cs (40PSI)
873-112	Styrofoam Blocks 4"x12"x12" (40PSI) 15/Cs
874-807	Diacor Styrofoam 3"x7 5/8"x7 5/8" 80/Cs (40PSI)
874-811	Diacor Styrofoam 3"x11 1/2 x11 1/2" (40 PSI) 32/Cs

MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT & COMPANY IDENTIFICATION

Page: 1

24-Hour Emergency Phone Number: 989-636-4400

Product: STYROFOAM* 3.00 X 48 Inch Panel Core 40 Extruded Foam
Insulation

SULATION BF

Product Code: 97824

Effective Date: 01/13/04 Date Printed: 06/16/04 MSD: 006839

The Dow Chemical Company, Midland, MI 48674

Customer Information Center: 800-258-2436

2. COMPOSITION/INFORMATION ON INGREDIENTS

Polystyrene	CAS# 009003-53-6
Chlorodifluoroethane	CAS# 000075-68-3
Copolymer mixtures	
Halogenated flame retardant	

This product may contain additives (such as magnesium silicate, CAS# 14807-96-6) generally at levels <1.5% maximum.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

* Blue rigid cellular foam board. Odorless. No significant *
* immediate hazards for emergency response are known. *

POTENTIAL HEALTH EFFECTS (See Section 11 for toxicological data.)

EYE: Solid or dust may cause irritation or corneal injury due to mechanical action.

SKIN: Essentially nonirritating to skin. Mechanical injury only. Skin absorption is unlikely due to physical properties.

INGESTION: Single dose oral toxicity is considered to be low. Small amounts swallowed incidental to normal handling operations are not likely to cause injury; swallowing amounts larger than that may cause injury. May cause choking or blockage of the digestive tract if swallowed.

(Continued on page 2 , over)

* OR (R) INDICATES A TRADEMARK OF THE DOW CHEMICAL COMPANY

Product: STYROFOAM* 3.00 X 48 Inch Panel Core 40 Extruded Foam
Insulation

SULATION BF
Product Code: 97824

Effective Date: 01/13/04 Date Printed: 06/16/04 MSD: 006839

INHALATION: Dust may cause irritation to upper respiratory tract (nose and throat). Vapors/fumes released during thermal operations such as hot wire cutting may cause eye and respiratory irritation. High concentrations of the blowing agents (>5000 ppm) may cause central nervous system, anesthetic or narcotic effects and cardiac sensitization (irregular heartbeats). Concentrations of the blowing agents anticipated incidental to proper handling are expected to be well below those which cause acute inhalation effects and below exposure guidelines. In animals, excessive exposure to chlorodifluoroethane (HCFC 142b) has caused low blood pressure, respiratory stimulation and chest tightness (broncho-constriction).

SYSTEMIC (OTHER TARGET ORGAN) EFFECTS: Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

CANCER INFORMATION: Neither polystyrene foam dust, nor chlorodifluoroethane (HCFC-142b) caused cancer in long-term animal studies.

TERATOLOGY (BIRTH DEFECTS): Contains component(s) which did not cause birth defects in laboratory animals. The component(s) is/are dichlorofluoroethane (HCFC-142b).

REPRODUCTIVE EFFECTS: No relevant information found.

4. FIRST AID

EYE: Flush eyes with plenty of water; mechanical effects only.

SKIN: Wash off in flowing water or shower.

INGESTION: If swallowed, seek medical attention. May cause gastrointestinal blockage. Do not give laxatives. Do not induce vomiting unless directed to do so by medical personnel.

INHALATION: Remove to fresh air. If not breathing give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

NOTE TO PHYSICIAN: No specific antidote. Supportive care. Treatment based on judgment of the physician in response to

(Continued on page 3)

* OR (R) INDICATES A TRADEMARK OF THE DOW CHEMICAL COMPANY

Product:STYROFOAM* 3.00 X 48 Inch Panel Core 40 Extruded Foam
Insulation

SULATION BF
Product Code: 97824

Effective Date: 01/13/04 Date Printed: 06/16/04 MSD: 006839

reactions of the patient. Exposure may increase "myocardial irritability". Do not administer sympathomimetic drugs unless absolutely necessary.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

FLASH POINT: 670F, 354C Flash ignition temperature.
METHOD USED: ASTM D1929 Proc. B.

FLAMMABILITY LIMITS

LFL: Not applicable.
UFL: Not applicable.

HAZARDOUS COMBUSTION PRODUCTS: In smoldering or flaming conditions, carbon monoxide, carbon dioxide and carbon are generated. Evolution of small amounts of hydrogen halides occur when burned or heated above 250C (480F). Under fire conditions polymers decompose. The smoke may contain polymer fragments of varying compositions in addition to unidentified and/or irritating compounds. Studies have shown that the products of combustion of this foam are not more acutely toxic than the products of combustion of common building materials such as wood.

OTHER FLAMMABILITY INFORMATION: This plastic foam product is combustible and should be protected from flames and other high heat sources. For more information contact Dow. Dense smoke is produced when product burns. When product is stored in closed containers a flammable atmosphere can develop. Container may vent and/or rupture due to fire. This product contains a flame retardant to inhibit accidental ignition from small fire sources. Mechanical cutting, grinding or sawing can cause formation of dusts. To reduce the potential for dust explosion, do not permit dust to accumulate.

EXTINGUISHING MEDIA: Foam, water, carbon dioxide, dry chemical.

FIRE FIGHTING INSTRUCTIONS: Keep people away. Isolate fire area and deny unnecessary entry. If material is molten, do not apply direct water stream. Use fine water spray or foam. Soak thoroughly with water to cool and prevent re-ignition. Cool surroundings with water to localize fire zone.

PROTECTIVE EQUIPMENT FOR FIRE FIGHTERS: Wear positive-pressure,

(Continued on page 4 , over)

* OR (R) INDICATES A TRADEMARK OF THE DOW CHEMICAL COMPANY

Product: STYROFOAM* 3.00 X 48 Inch Panel Core 40 Extruded Foam
Insulation

SULATION BF
Product Code: 97824

Effective Date: 01/13/04 Date Printed: 06/16/04 MSD: 006839

self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, pants, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

6. ACCIDENTAL RELEASE MEASURES (See Section 15 for Regulatory Information)

PROTECT PEOPLE: Clear non-emergency personnel from area. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls/Personal Protection.

PROTECT THE ENVIRONMENT: Fire water run off may be toxic.

CLEANUP: Pick up, or if dust or in small pieces, sweep up and place in suitable container for disposal. See Section 13, Disposal Considerations.

7. HANDLING AND STORAGE

HANDLING: Maintain good housekeeping. Layers of flammable dusts should not be permitted to accumulate. See Section 8, Exposure Controls/Personal Protection.

WARNING: In order to prevent buildup of combustible vapors, do not store large quantities of this product in unventilated spaces. Transport bulk shipments of this product in ventilated vehicles.

STORAGE: Flammable vapors may accumulate in some storage situations. Storage, use and handling areas should be "No Smoking" areas. See Section 8, Exposure Controls/Personal Protection. See Section 10, Stability and Reactivity.

Minimize sources of ignition, such as static buildup, heat, spark or flame.

When storing or fabricating large quantities of extruded polystyrene foam, the blowing agents (i.e. chlorodifluoroethane) released from the foam, if any, may thermally decompose to hydrogen chloride, which tends to accelerate corrosion or rust development of heaters, boilers, gas fired recirculating air furnaces or heaters, or gas water heaters.

(Continued on page 5)

* OR (R) INDICATES A TRADEMARK OF THE DOW CHEMICAL COMPANY

Product:STYROFOAM* 3.00 X 48 Inch Panel Core 40 Extruded Foam
Insulation

SULATION BF
Product Code: 97824

Effective Date: 01/13/04 Date Printed: 06/16/04 MSD: 006839

This polystyrene foam plastic product is combustible and should be protected from flame and other high heat sources. It should be installed with code-acceptable thermal barriers or used in approved alternative constructions.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Provide general and/or local exhaust ventilation to control airborne levels below the exposure guidelines.

PERSONAL/PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION: Use safety glasses. If there is a potential for exposure to particles which could cause mechanical injury to the eye, wear chemical goggles.

SKIN PROTECTION: No precaution other than clean body-covering clothing should be needed.

RESPIRATORY PROTECTION: Atmospheric levels should be maintained below the exposure guideline. When respiratory protection is required for certain operations, including but not limited to saw, router, or hot wire cutting, use an approved air-purifying respirator. In dusty atmospheres, use an approved dust respirator.

EXPOSURE GUIDELINE(S): 1-Chloro-1,1-difluoroethane (HCFC 142b):
AIHA WEEL is 1000 ppm, TWA.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE/PHYSICAL STATE: Blue rigid cellular foam board.
ODOR: Odorless
VAPOR PRESSURE: Not applicable
VAPOR DENSITY: Not applicable
BOILING POINT: Not applicable
SOLUBILITY IN WATER/MISCIBILITY: None
SPECIFIC GRAVITY OR DENSITY: .027 To .064

10. STABILITY AND REACTIVITY

STABILITY: Thermally stable at typical use temperatures.

CONDITIONS TO AVOID: Avoid direct sunlight. Maximum use

(Continued on page 6 , over)

* OR (R) INDICATES A TRADEMARK OF THE DOW CHEMICAL COMPANY

Product: STYROFOAM* 3.00 X 48 Inch Panel Core 40 Extruded Foam
Insulation

SULATION BF

Product Code: 97824

Effective Date: 01/13/04

Date Printed: 06/16/04

MSD: 006839

temperature 73C (165F). Avoid temperatures above 300C (572F).
Product can decompose at elevated temperatures.

INCOMPATIBILITY WITH OTHER MATERIALS: Avoid contact with
oxidizing materials. Avoid contact with aldehydes, amines,
esters, liquid fuels, organic solvents.

HAZARDOUS DECOMPOSITION PRODUCTS: Does not normally decompose.
Evolution of small amounts of hydrogen halides occur when
heated above 250C. Under high heat, non-flaming conditions,
small amounts of aromatic hydrocarbons such as styrene and
ethylbenzene are generated. Hazardous decomposition products
depend upon temperature, air supply and the presence of other
materials. Hazardous decomposition products may include and
are not limited to ethylbenzene, aromatic compounds, aldehydes,
hydrogen bromide, hydrogen chloride, hydrogen fluoride, polymer
fragments, styrene.

HAZARDOUS POLYMERIZATION: Will not occur.

11. TOXICOLOGICAL INFORMATION (See Section 3 for Potential Health
Effects. For detailed toxicological data, write or call the
address or non-emergency number shown in Section 1)

MUTAGENICITY: For the minor component(s) dichlorofluoroethane
(HCFC 142b), in vitro mutagenicity studies were negative in
some cases and positive in other cases. Animal mutagenicity
studies were negative.

12. ECOLOGICAL INFORMATION (For detailed Ecological data, write or call
the address or non-emergency number shown in Section 1)

ENVIRONMENTAL FATE

MOVEMENT & PARTITIONING: No bioconcentration is expected
because of the relatively high molecular weight (MW greater
than 1000). In the terrestrial environment, material is
expected to remain in the soil. In the aquatic environment,
material is expected to float. Based largely or completely
on information for flame retardant. There is no evidence
of any significant leaching, therefore it is unlikely to
contaminate groundwater.

DEGRADATION & PERSISTENCE: Surface photodegradation is
expected with exposure to sunlight. No appreciable

(Continued on page 7)

* OR (R) INDICATES A TRADEMARK OF THE DOW CHEMICAL COMPANY

Product: STYROFOAM* 3.00 X 48 Inch Panel Core 40 Extruded Foam
Insulation

SULATION BF
Product Code: 97824

Effective Date: 01/13/04 Date Printed: 06/16/04 MSD: 006839

biodegradation is expected. Based largely or completely on information for blowing agent. Chlorodifluoroethane (HCFC 142b) remains in the foam and diffuses out slowly, most of it degrading in the troposphere to CO₂, HCl and HF. Chlorodifluoroethane (HCFC 142b) has a stratospheric ozone depletion potential (ODP) of 0.065, relative to CFC 12 (ODP=1).

ECOTOXICITY: Not expected to be acutely toxic.

13. DISPOSAL CONSIDERATIONS (See Section 15 for Regulatory Information)

DISPOSAL: All disposal methods must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. THE DOW CHEMICAL COMPANY HAS NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION 2 (Composition/Information On Ingredients).

FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: recycler, reclaimer, incinerator or other thermal destruction device, landfill.

For additional information, refer to Handling & Storage Information, MSDS Section 7.

As a service to its customers, Dow can provide names of information resources to help identify waste management companies and other facilities which recycle, reprocess or manage chemicals or plastics, and that manage used drums. Telephone Dow's Customers Information Center at 800-258-2436 or 989-832-1556 for further details.

14. TRANSPORT INFORMATION

DEPARTMENT OF TRANSPORTATION (D.O.T.): This product is not regulated by D.O.T. when shipped domestically by land.

CANADIAN TDG INFORMATION: This product is not regulated by TDG when shipped domestically by land.

15. REGULATORY INFORMATION (Not meant to be all-inclusive--selected regulations represented)

(Continued on page 8 , over)

* OR (R) INDICATES A TRADEMARK OF THE DOW CHEMICAL COMPANY

Product: STYROFOAM* 3.00 X 48 Inch Panel Core 40 Extruded Foam
Insulation

SULATION BF
Product Code: 97824

Effective Date: 01/13/04 Date Printed: 06/16/04 MSD: 006839

NOTICE: The information herein is presented in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied is given. Regulatory requirements are subject to change and may differ from one location to another; it is the buyer's responsibility to ensure that its activities comply with federal, state or provincial, and local laws. The following specific information is made for the purpose of complying with numerous federal, state or provincial, and local laws and regulations. See other sections for health and safety information.

U.S. REGULATIONS

=====

SARA 313 INFORMATION: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

CHEMICAL NAME	CAS NUMBER	CONCENTRATION
CHLORODIFLUOROETHANE	000075-68-3	<15 %

SARA HAZARD CATEGORY: This product has been reviewed according to the EPA "Hazard Categories" promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Not to have met any hazard category

STATE RIGHT-TO-KNOW: The following product components are cited on certain state lists as mentioned. Non-listed components may be shown in the composition section of the MSDS.

CHEMICAL NAME	CAS NUMBER	LIST
CHLORODIFLUOROETHANE	000075-68-3	NJ2 PA1 NJ3
TALC	014807-96-6	PA1 NJ3

(Continued on page 9)

* OR (R) INDICATES A TRADEMARK OF THE DOW CHEMICAL COMPANY

Product:STYROFOAM* 3.00 X 48 Inch Panel Core 40 Extruded Foam
Insulation

SULATION BF
Product Code: 97824

Effective Date: 01/13/04 Date Printed: 06/16/04 MSD: 006839

REGULATORY INFORMATION (CONTINUED)

NJ2=New Jersey Environmental Hazardous Substance (present at greater than or equal to 1.0%).

NJ3=New Jersey Workplace Hazardous Substance (present at greater than or equal to 1.0%).

PA1=Pennsylvania Hazardous Substance (present at greater than or equal to 1.0%).

OSHA HAZARD COMMUNICATION STANDARD:

This product is not a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

CANADIAN REGULATIONS

=====

WHMIS INFORMATION: The Canadian Workplace Hazardous Materials Information System (WHMIS) Classification for this product is:

This product is not a "Controlled Product" under WHMIS.

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA):

All substances in this product are listed on the Canadian Domestic Substances List (DSL) or are not required to be listed.

16. OTHER INFORMATION

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) RATINGS:

Health	0
Flammability	1
Reactivity	0

MSDS STATUS: Revised Section 16.

For further information, contact the Plastics Customer Information Group at 1-866-583-BLUE(2583).

* OR (R) INDICATES A TRADEMARK OF THE DOW CHEMICAL COMPANY
The Information Herein Is Given In Good Faith, But No Warranty, Express Or Implied, Is Made. Consult The Dow Chemical Company For Further Information.