



Radiation Products Design, Inc.

5218 Barthel Industrial Drive

Albertville, MN 55301

www.rpdinc.com

Phone: 800-497-2071 Fax: 763-497-2295

**RPD is an
authorized distributor**


RPD Product Information

Item Number Description

300-210-A2	* Exradin Model A2 - 0.5cc Spokas Thimble Chamber
300-210-M2	* Exradin Model M2 - 0.5cc Spokas Thimble Chamber
300-210-P2	* Exradin Model P2 - 0.5cc Spokas Thimble Chamber
300-210-T2	* Exradin Model T2 - 0.5cc Spokas Thimble Chamber

Model 2 - Spokas Thimble Chamber

- Axially symmetric design
- High collection efficiency
- Homogeneous construction
- Complete guarding
- Waterproof construction
- Gas flow capability
- Integral flexible low-noise cable
- Separable minimum scatter stem
- Matching equilibrium caps
- Handsome wooden case



Features

Collecting Volume: 0.5 cm³

Centroid of Collecting Volume: 7.0 mm from tip of chamber

Collector Diameter: 4.6 mm

Outside Diameter Sensitive Region: 11.5 mm

Wall Thickness: 1.0 mm

Wall, Collector, and Guard Material:

Model A2 – Shonka air-equivalent plastic C552

Model M2 – Magnesium

Model P2 – Polystyrene Equivalent

Model T2 – Shonka tissue-equivalent plastic A150

Maximum Polarizing Potential: Greater than 1000 V

Inherent Leakage Currents: Less than 10^{-15} Amperes

Cable: 50 Ohms, 29pF/f, 2 m long

Signal Connector: Choice of coaxial and triaxial BNC plugs and jacks and triaxial TNC plug

High Voltage Connector: Integral with triaxial connectors (shell of chamber is common with connector body). Banana, MHV, and SHV plugs are also available.

Vent Tubes: Two 21 Ga stainless steel tubes which may be extended to connector via 22 Ga TFE tubing for possible immersion in liquid phantoms.

Stem: Black phenolic, 0.5 in OD by 9, 5, or 4 in long. Two-piece stem consisting of a 4 in segment at chamber and a 5 in segment threaded together is also available.