

Safety Data Sheet

E206 Silicone Mold Release™

Stoner

Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

1. IDENTIFICATION

Stoner Incorporated
1070 Robert Fulton Hwy.
Quarryville, PA 17566
1-800-227-5538

Product Name: Silicone Mold Release™
Product Code: E206
Product Use: Mold Release
24-hour emergency phone: 1-800-424-9300 [CHEMTREC]

2. HAZARD IDENTIFICATION

POTENTIAL HEALTH EFFECTS

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard
Symbols



GHS Classification

Gases under pressure - Liquefied Gas
Flammable Aerosol Category 2

Signal Word

Warning

Hazard Statements

Flammable aerosol.
Contains gas under pressure; may explode if heated.

Precautionary Statements

Prevention

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.

Storage

Protect from sunlight. Store in a well-ventilated place.
Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.

3. COMPOSITION/INFORMATION ON INGREDIENTS

| COMPONENT | CAS # | Percent |
|-------------------------------------|---------|---------|
| Halogenated hydrocarbon/ether blend | Mixture | 80-100 |

HMIS® III* HAZARDOUS WARNINGS:

| | | | | |
|-----------|-----------------|-------------|--------------------------------|---------------|
| Health: 1 | Flammability: 2 | Physical: 2 | Personal Protective Equipment: | See Section 8 |
|-----------|-----------------|-------------|--------------------------------|---------------|

* See www.paint.org/hmis or call the NPCA at 1 (202) 462-6272 for more information on this current rating system.

4. FIRST AID MEASURES

Eyes: Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there is visual difficulty, seek medical attention.

Skin Contact: In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. For liquid contact, treat for frostbite if necessary. Seek medical attention if symptoms persist. Wash clothing before reuse.

Ingestion: Ingestion is an unlikely route of exposure. Contact a physician, medical facility, or poison control center for advice on whether to induce vomiting. Never give anything by mouth if victim is rapidly losing consciousness or is unconscious or convulsing.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek immediate medical attention.

NOTES TO PHYSICIAN:

Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used only in situations of emergency life support.

5. FIRE FIGHTING MEASURES

| | |
|--------------------------------|---|
| Fire and/or Explosion Hazards: | This product contains a component(s) that is considered an extremely flammable gas(es), which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. Containers may rupture or explode under fire conditions. |
| Fire Fighting Instructions: | Use CO ₂ , foam or dry chemical. Water is generally not effective and may spread fire; however, water spray may be used from a safe distance to cool closed containers and protect surrounding area. |

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Ventilate contaminated area. Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Avoid run-off into storm sewers and ditches which may lead to natural waterways. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly. If runoff occurs, notify authorities as required.

7. HANDLING AND STORAGE

| | |
|-----------|---|
| Handling: | Use with adequate ventilation. Do not use near ignition sources. Avoid prolonged or repeated contact with skin. Avoid prolonged or repeated breathing of vapor. May cause frostbite. |
| Storage: | Store in a cool, dry, well ventilated area away from all sources of ignition. Do not store at temperatures above 120 degrees F. Empty container may contain residues which are hazardous. Store away from incompatible materials such as materials that support combustion (oxidizing materials) and corrosive materials (strong acids or bases). Store away from oxygen cylinders or other oxidizing materials and possible ignition sources. Ground all equipment and cylinders before use. |

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

| | |
|-------------------------|--|
| Engineering Controls: | Ventilation should be adequate to prevent exposures above the limits indicated below in this section of the SDS (from known, suspected or apparent adverse effects). |
| Eye Protection: | Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Have an eye wash station available. |
| Skin Protection: | The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with skin. |
| Respiratory Protection: | A supplied air respirator should be used if ventilation is not sufficient to maintain exposure limits. Use NIOSH approved respirator where there is likelihood of inhalation of the product mist, spray or aerosol. |

| <u>COMPONENT</u> | <u>CAS #</u> | <u>ACGIH TLV</u> | <u>OSHA PEL</u> | <u>OTHER</u> |
|-------------------------------------|--------------|------------------|-----------------|--------------------|
| Halogenated hydrocarbon/ether blend | Mixture | Not established | Not established | 1000ppm TWA (Mfr.) |

9. PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|------------------------------|-------------------|--|-------------------|
| Physical State: | Aerosol can | Lower Flammability Limit (%): | Not applicable |
| Appearance: | Clear Colorless | Upper Flammability Limit (%): | Not applicable |
| Odor: | Slight ethereal. | Vapor Pressure (PSIG @ 70°F): | 78.00 |
| Odor Threshold: | Mild | Vapor Density [air = 1]: | >1 |
| pH: | Not applicable | Relative Density (H ₂ O=1): | 0.8 |
| Melting/Freezing Point (°F): | No data available | Solubility in Water: | Negligible; 0-1% |
| Boiling Point (°F): | No data available | Partial Coefficient: n-octanol/water: | No data available |
| Flash Point (°F PMCC): | Not applicable | Autoignition Temperature (°F): | Not applicable |
| Evaporation Rate: | | Decomposition Temperature (°F): | No data available |
| Flammability (solid, gas): | No data available | Viscosity, dynamic (cSt): | No data available |
| Percent VOCs (%): | 40 - 60 | | |

10. STABILITY AND REACTION

| | |
|-------------------------|---|
| Chemical Stability: | Stable. |
| Conditions to Avoid: | Avoid contact with: Alkali. Alkaline earth metals. Freshly abraded aluminum surfaces. Powdered metals. Ignition sources such as open flames, sparks, static discharges or glowing metal surfaces. Oxidizers. Acetic acids Organic acid anhydrides. |
| Decomposition Products: | This material can be decomposed by extremely high temperatures (open flames, glowing metal surfaces, etc.) forming hydrofluoric acid and carbonyl fluoride. If heated with peroxides present, violent decomposition can occur. When heated to temperatures above 150°C in the presence of air, one of the ingredients in this product can form formaldehyde vapors. Formaldehyde vapor is harmful by inhalation; irritating to eyes; sensitizer to the respiratory system; an acute toxicant and a potential cancer hazard at concentrations greater than 0.75 ppm. |

11. TOXICOLOGICAL INFORMATION

| | |
|--|--------------------|
| Reproductive & Developmental Toxicity: | No data available. |
|--|--------------------|

| <u>Ingredient</u> | <u>CAS #</u> | <u>Toxicological Data</u> |
|-------------------------|--------------|---|
| Halogenated hydrocarbon | Mixture | ORAL ALD Rat > 1500 mg/kg 4HR ALC Rat 383000 ppm |
| Ether propellant | 115-10-6 | Inhalation LC50 Rat = 164000 ppm |

12. ECOLOGICAL INFORMATION

Ecological Toxicity: No data available
Mobility: No data available

Ingredient
Ether propellant

CAS #
115-10-6

Toxicological Data
48HR NOEC GUPPIES > 4000 mg/L
48HR NOEC Daphnia > 4000 mg/L

13. DISPOSAL CONSIDERATIONS

Disposal : Dispose according to Federal, State and local regulations.

14. TRANSPORTATION INFORMATION

| Agency | UN Number | Proper Shipping name | Hazard Class | Packing Group |
|--------|-----------|---------------------------|--------------|----------------|
| DOT | | Aerosols, Non- Flammable† | ORM-D | Not applicable |
| IATA | ID8000 | Consumer Commodity† | 9 | Not applicable |
| IMDG | UN1950 | Aerosols, Non- Flammable† | 2.2 | Not applicable |

† "Limited Quantities" may be applicable for this transportation mode.

15. REGULATORY INFORMATION

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:

| COMPONENT | CAS # | % BY WEIGHT | Regulatory Body |
|---------------------------------------|-------|-------------|-----------------|
| No components listed in this section. | | | |

Warning: This product may contain chemicals known to the State of California to cause cancer. See list below.

| COMPONENT | CAS # | % BY WEIGHT | Regulatory Body |
|--------------|----------|-----------------|-----------------|
| Benzene | 71-43-2 | 0.00001- 0.0001 | Prop65 Cancer |
| Cumene | 98-82-8 | 0.00001- 0.0001 | Prop65 Cancer |
| Naphthalene | 91-20-3 | 0.00001- 0.0001 | Prop65 Cancer |
| ETHYLBENZENE | 100-41-4 | 0.00001- 0.0001 | Prop65 Cancer |

Warning: This product may contain chemicals known to the State of California to cause birth defects. See list below.

| COMPONENT | CAS # | % BY WEIGHT | Regulatory Body |
|-----------|----------|-----------------|----------------------|
| Toluene | 108-88-3 | 0.0001- 0.001 | Prop65 Birth Defects |
| Benzene | 71-43-2 | 0.00001- 0.0001 | Prop65 Birth Defects |

All components of this product are listed on the TSCA inventory.

16. OTHER INFORMATION

Other Information : SDS Prepared by L. Dean Swartz, SDS Coordinator

Version Date: 03/24/16

This information contained in this SDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.